



Product: **Linear Alkyl Benzene (L.A.B)**

Packing: Bulk/ Drum/ Iso Tank

PRODUCT SPECIFICATION			
Properties	Unit	Test Method	Specification
T.N.P	wt%	UOP 698	0.5 max
LAB 9	wt%	UOP 698	<1
LAB 10	wt%	UOP 698	15 max
LAB 11	wt%	UOP 698	24-44
LAB 12	wt%	UOP 698	22-36
LAB 13	wt%	UOP 698	17-27
LAB 14	wt%	UOP 698	<1
Total LAB	wt%	UOP 698	92 min
Non LAB	wt%	UOP 698	<7
LAB 14+	wt%	UOP 698	0.5 max
HAB	wt%	UOP 698	-
A.M.W	-	UOP 698	238-244
2-Phenyl %	wt%	UOP 698	20 max
Br.Index	Mg/100g	ASTM D1492	10 max
Water	ppm	ASTM D6304	200 max
Refractive.index	-	ASTM D1218	1.4800-1.4900
Density (15.6°C)	gr/cm ³	ASTM D4052	0.8550-0.870
Tetraline	wt%	Ecosol Method	1 max
Dr Test	-	ASTM D484	Negative
Sulfonability	%	UOP 429	98 min
Colour	SYB	ASTM D156	29 min
Viscosity (40°C)	CP	ASTM D444	<10

WWW.WORLDARCHEXIM.COM

WORLDARCH EXIM PVT. LTD.

Flat No. EWS-GF08. La Lagune, Sector54, Golf Course Road, Gurgaon Haryana-122002 India