



Product: **Rubber Process Oil**

Grade: **RAE 60 (Heavy)**

Packing: Bulk/ Iso Tank/ Flexi Tank/ Drum

Producer: Iranol Oil Co.

| <b>PRODUCT SPECIFICATION</b>             |               |                         |
|--|---------------|-------------------------|
| <b>Characteristic</b>                    | <b>Result</b> | <b>Test method ASTM</b> |
| Kinematic Viscosity @ 100°C              | 60            | D-445                   |
| Flash Point, °c                          | 300           | D-92                    |
| Pour Point, °C                           | 20            | D-97                    |
| Specific gravity @ 15, kg/m <sup>3</sup> | 995           | D-1298                  |
| Aniline point, °c                        | 65            | IP-2                    |
| Sulphur content, Wt%                     | 5             | D-2622                  |
| Ash content                              | 0.15          | D-482                   |
| Carbon type analysis, %                  |               |                         |
| C <sub>A</sub>                           | 35            | D-3238                  |
| C <sub>N</sub>                           | 5             |                         |
| C <sub>P</sub>                           | 60            |                         |

[WWW.WORLDARCHEXIM.COM](http://WWW.WORLDARCHEXIM.COM)

**WORLDARCH EXIM PVT. LTD.**

Flat No. EWS-GF08. La Lagune, Sector54, Golf Course Road, Gurgaon Haryana-122002 India